

Transporter RF Digitizer

Ideal for converting analog signal into digital packets to stream satellite signals across the world

Transporter converts analog signals into digital samples that can be transferred across any IP network. When the packets arrive at their destination, the samples can be processed digitally or restored to the original analog signal.

The HTML5-based user interface allows Transporter to be operated from all browsers and on all platforms including Android and IOS devices. With powerful internal FPGA processing, Transporter uses state-of-the-art digital technology to preserve signal quality and timing.

Transporter has a very low noise floor and a large dynamic range that's ideal for digitizing any type of satellite carrier in a gateway, teleport or broadcast facility. It accepts all signals from 450 MHz to 4.0 GHz, and input power levels can range from -60 to +5 dBm, making Transporter ideal for digitizing both high and low power satellite signals. Transporter is signal agnostic, so FDMA, TDMA and CDMA signals from satellites of all different types of orbits (GEO, MEO, LEO) are supported. Transporter can be connected to an external 10 MHz reference for improved frequency accuracy and stability, and to assist in preserving signal timing.

The powerful Graphical User Interface (GUI) is available using any HTML5 standard web browser, no additional software is required. All data communications from the user interface occurs securely via the built-in Ethernet port using HTTPS. Transporter provides network access to all staff connected to the facility network or a corporate wide area network, so users can configure and monitor the unit any time and from any location in the world using only a web browser. For integration into a larger system, Transporter can be automated through a REST or SNMP API.



Potential applications for the Transporter satellite communications digitizer are numerous, but some of the potential uses cases are:

- Virtualization
- Digitalization
- Site Diversity
- Security
- Monitoring
- Recording

Advantages of the Digital IF (RF over IP) technology found inside Transporter include:

- Scalability
- Flexibility
- Efficiency
- Enhanced signal quality
- Resiliency
- Reliability
- Interoperability (DIFI standards-based)
- Mechanical performance

Transporter Specifications

Overview

- Full satellite L/S-band from 450 MHz to 4.0 GHz
- 2 input and 2 output ports, 50 ohm SMA
- Up to 500 MHz bandwidth per port
- 2 SFP/QSFP 10/25/100 GbE ports
- DIFI standards compliant
- Standard 19" 1RU
- External 10 MHz reference or internal reference
- Web browser and/or REST API control
- SNMP status interface

Physical Interfaces

RF Inputs	2 x SMA 50 ohms
RF Inputs	2 x SMA 50 ohms
Data Interface	2 x SFP/QSFP, 10/25/100 GigE
Control	RJ-45, 1 GigE
Reference	BNC, 50 ohms
AC Power	IEC 60320 (qty 2, redundant)

Chassis

Height	4.4 cm (1.75")
Width	48.5 cm (19 1/8")
Depth	30.0 cm (12")
Weight	4.4 kg (10 lbs)

RF Input / Output

Frequency Range	450 MHz to 4.0 GHz
Input Range	-60 to +5 dBm (aggregate)
Output Range	-30 to +5 dBm (aggregate)
Maximum Safe Input	+10 dBm
Input Isolation (port to port)	60 dB (min)
Input Return Loss	-15 dB (min)
Output Isolation (port to port)	55 dB (min)
Output Return Loss	-15 dB (min)
Spurious Images	< -50 dBc (typical)
Spurious Aliasing	< -50 dBc (typical)
Phase Noise (worst case at 4 GHz)	-89 dBc/Hz at 1 kHz offset -91 dBc/Hz at 100 kHz offset -124 dBc/Hz at 1 MHz offset

Certifications

EMC/EMI	EN 61326-1 FCC Title 47, Part 15
Safety	EN 61010-1 UL 61010-1 CSA22.2 No. 61010-1
Other	CE, ROHS3, REACH

Data Interface

Sample Rate	12.5 ksps-625 Msps
Bandwidth	10 kHz-500 MHz
Input Channels	Up to 16
Output Channels	Up to 16
Signal Resolution	4-14 bits
Frequency Resolution	1 Hz

Other Specifications

Power Requirements	90-264 VAC, 50/60 Hz, 75W
Operational Temperature	0 to 40°C
Operating Humidity	0% to 85% (non-condensing)
Reference Input	10 MHz, -3 dBm to +13 dBm, +3 dBm to +13 dBm (auto-sensing)
Control Interface	TCP/IP, API, SNMP, HTTPS

Notes

1. All specification at 25°C unless otherwise noted and are subject to change without notice.

