

4m SATCOM Antenna

Calian offers a 4m antenna system that is suitable for many SATCOM applications, including gateways, TT&C, or diversity stations. The motion control system in this antenna makes it capable of tracking geo-synchronous and inclined geo-synchronous orbits. This antenna has been deployed widely and is field-proven. The antenna can be fitted with several different feeds to support your application. Our ground station integration experience in the satellite industry means this antenna is designed to meet the needs of your network.

Specifications

General Configuration

Configuration:	Cassegrain, Ring Focus and Prime Focus designs 2 axis motion, elevation over azimuth
Main reflector:	4m diameter Precision formed aluminum Surface accuracy below 0.008" RMS
Sub reflector:	High accuracy composite Surface accuracy below 0.002" RMS
Hub:	Up to 4 ft. diameter for RF equipment integration available upon request
Pedestal:	High stiffness reinforced pedestal
Optional:	De-icing system Environmentally controlled hub Adjustable polarization

M&C Interface

Ethernet interface for M&C and user interface

Full remote operation and monitoring with multiple tracking options

The antenna can be controlled via the provided computer software application or via a customer interface

Mechanical Performance

Pointing accuracy:	0.005°
Speed:	1°/s in azimuth 0.5°/s in elevation
Acceleration:	0.5°/s ² in both axis
Travel range:	±200° in azimuth 0°-90° in elevation
Drives:	Dual torque biased in azimuth Precision jack drive in elevation

Power

Drive Systems:	208VAC 50/60Hz 3-phase
De-icing System:	208/220 3 phase
Auxiliary Circuits:	208VAC split phase 60 Hz 220VAC single phase 50 Hz (optional)

Feed Options

Supports single, dual, tri-band feeds, e.g., S to V, S/X, C/Ku, X/Ku, Ku/Ka, Q/V, S/X/Ka, etc.

CP and LP Broadband feed options available

Tracking Options

Multiple open and closed loop tracking options include: Table track, NORAD TLE, IESS-412,

Monopulse (optional), Step Track (optional)



Environmental Performance

Temperature:	Operational -30 to +60 °C Survival -40 to +70 °C
Seismic:	0.3g horizontal and vertical
Wind speed:	Operational, up to 100 km/h (62 mph) Survival, 200 km/h (125 mph) in stow position
Humidity:	0 to 100% with condensation
Ice Accumulation:	30mm thick on all exposed surfaces
Corrosion:	Galvanized ASTM-A123, Stainless and Galvanized Fasteners, multi-layer epoxy-based paint

Shipping Configuration and Features

Modular design to allow for easy shipping in standard containers or crate.

Rapid deployment, assembly, and commissioning at customer site.



Ka-Band Performance

	Rx	Tx
Frequency (GHz)	17.70 - 21.50	27.50 - 31.00
Feed Ports	2CP + 2 Monopulse	2CP
Antenna Gain	57.29 dBi @21.5 GHz	60.38 dBi @31 GHz
Beamwidth @ -3dB	0.28°	0.19°
G/Ts at Clear Sky with 120 K LNA @ 20° Elevation		
17.70 GHz	32.61 dB/K	
19.60 GHz	33.35 dB/K	
21.50 GHz	33.63 dB/K	
Power handling, per port (CW)	500 watts	500 watts
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation (Axial Ratio)	32.78 dB (1.047)	32.78 dB (1.047)
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

Ku-Band Performance

	Rx	Tx
Frequency (GHz)	10.70 – 12.75	12.70 – 14.50
Feed Ports	2LP + 2 Monopulse	2LP
Antenna Gain	52.73 dBi @12.75 GHz	53.97 dBi @14.50 GHz
Beamwidth @ -3dB	0.47°	0.40°
G/Ts at Clear Sky with 59 K LNA @ 20° Elevation		
10.70 GHz	30.34 dB/K	
11.75 GHz	31.10 dB/K	
12.75 GHz	31.78 dB/K	
Power handling, per port (CW)	500 watts	500 watts
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation	35 dB	35 dB
Port to Port Isolation $R_x \rightarrow T_x, T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x, T_x \rightarrow T_x$	35 dB	35 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

X-Band Performance

	Rx	Tx
Frequency (GHz)	7.25 – 7.75	7.90 – 8.40
Feed Ports	2CP + 2 Monopulse	2CP
Antenna Gain	48.48 dBi @7.75 GHz	49.17 dBi @8.40 GHz
Beamwidth @ -3dB	0.73°	0.67°
G/Ts at Clear Sky with 50 K LNA @ 10° Elevation		
7.25 GHz	27.53 dB/K	
7.50 GHz	27.82 dB/K	
7.75 GHz	28.09 dB/K	
Power handling, per port (CW)	500 watts	500 watts
VSWR (Feed interface)	1.30	1.30
Cross Pol Isolation (Axial Ratio)	32.78 dB (1.047)	32.78 dB (1.047)
Port to Port Isolation $R_x \rightarrow T_x, T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x, T_x \rightarrow T_x$	18 dB	18 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

C-Band Performance

	Rx	Tx
Frequency (GHz)	3.400 – 4.200	5.725 – 6.725
Feed Ports	2CP + 2 Monopulse	2CP
Antenna Gain	43.38 dBi @4.200 GHz	47.45 dBi @6.725 GHz
Beamwidth @ -3dB	1.44°	0.88°
G/Ts at Clear Sky with 30 K LNA @ 20° Elevation		
3.400 GHz	22.33 dB/K	
3.800 GHz	23.29 dB/K	
4.200 GHz	24.16 dB/K	
Power handling, per port (CW)	500 watts	500 watts
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation (Axial Ratio)	32.78 dB (1.047)	32.78 dB (1.047)
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

S-Band Performance

	Rx	Tx
Frequency (GHz)	2.170 – 2.300	1.980 – 2.120
Feed Ports	2CP + 2 Monopulse	2CP
Antenna Gain	38.16 dBi @2.300 GHz	37.45 dBi @2.120 GHz
Beamwidth @ -3dB	2.44°	2.66°
G/Ts at Clear Sky with 45 K LNA @ 20° Elevation		
2.170 GHz	17.48 dB/K	
2.235 GHz	17.74 dB/K	
2.300 GHz	17.99 dB/K	
VSWR (Feed interface)	1.25	1.25
Cross Pol Isolation (Axial Ratio)	32.78 dB (1.047)	32.78 dB (1.047)
Port to Port Isolation $R_x \rightarrow T_x$, $T_x \rightarrow R_x$	85 dB	85 dB
Port to Port Isolation $R_x \rightarrow R_x$, $T_x \rightarrow T_x$	20 dB	20 dB
Sidelobes	Meets ITU-R S-580-6	Meets ITU-R S-580-6

Contact Rob or Mohamed today.

Rob Vance, Director, Satellite Antenna Ground Systems, T: 408-221-5728

Mohamed Saad, President, Calian InterTronic, T: 450 424-5666

E: antennas@calian.com

www.calian.com/products/group/antenna

