

# 10m–15m High performance antenna

Calian high performance antennas are platforms intended for a wider variety of applications beyond satcom, including electronic warfare, radar, astronomy, and fast-target tracking. These antenna platforms combine high-slew-rate motion systems, and adaptable antenna interfaces to accommodate different applications and frequencies. We offer high accuracy optics with optimized reflector shaping for elevated efficiency. Advanced control systems can be adapted to user requirements, enabling a variety of tracking or targeting capabilities.

## Specifications

### General configuration

Configuration	<ul style="list-style-type: none"> <li>Dual reflector Cassegrain design</li> <li>2 axis motion, elevation over azimuth</li> </ul>
Main reflector	<ul style="list-style-type: none"> <li>10 - 15m diameter</li> <li>Precision formed aluminum</li> <li>Surface accuracy below 0.008 RMS</li> </ul>
Sub reflector	<ul style="list-style-type: none"> <li>High accuracy composite</li> <li>Surface accuracy below 0.002 RMS</li> </ul>
Hub	<ul style="list-style-type: none"> <li>Up to 10 ft. diameter for RF equipment integration available upon request</li> </ul>
Pedestal	<ul style="list-style-type: none"> <li>State of the art cable wrap systems with ample space for customer cables</li> </ul>
Optional	<ul style="list-style-type: none"> <li>Platform with staircase and hoist</li> <li>De-icing system</li> <li>Environmentally controlled hub</li> </ul>

### M&C interface

- Ethernet interface for M&C and user interface.
- Full remote operation and monitoring with multiple tracking options.
- The antenna can be controlled via the provided computer software application or via a customer interface.

### Mechanical performance

Speed	<ul style="list-style-type: none"> <li>up to 12°/s in azimuth</li> <li>up to 6°/s in elevation</li> </ul>
Acceleration	<ul style="list-style-type: none"> <li>3°/s<sup>2</sup> in both axis</li> </ul>
Travel range	<ul style="list-style-type: none"> <li>±270° in azimuth (540° continuous)</li> <li>0°-90° in elevation</li> </ul>
Drives	<ul style="list-style-type: none"> <li>Dual torque biased backlash-free in both axes</li> </ul>

### Power

Drive systems	<ul style="list-style-type: none"> <li>380 to 480VAC 50/60Hz 3-phase</li> </ul>
De-icing system	<ul style="list-style-type: none"> <li>208/220 3 phase</li> </ul>
Auxiliary circuits	<ul style="list-style-type: none"> <li>208VAC split phase 60Hz</li> <li>220VAC single phase 50Hz (optional)</li> </ul>

### Optional frequency bands

- Supports single, dual, and multi-band feeds, e.g., S to Ka, S/X, C/Ku, X/Ku, X/Ka, Ku/Ka, etc.
- CP and LP Broadband feed options available

### Tracking options

- Multiple open and closed loop tracking options include: Program track, NORAD TLE, IESS-412, Monopulse (optional), Step Track (optional)





## Environmental performance

<b>Temperature</b>	<ul style="list-style-type: none"> <li>Operational -30 to +60°C</li> <li>Survival -40 to +70 °C</li> </ul>
<b>Seismic</b>	<ul style="list-style-type: none"> <li>0.3g horizontal and vertical</li> </ul>
<b>Wind speed</b>	<ul style="list-style-type: none"> <li>Operational, up to 100 kph gusting (62 mph gusting)</li> <li>Survival, up to 200 km/hr (125 mph) in stow position</li> <li>Drive-to-stow, 125 kph (77 mph)</li> </ul>
<b>Humidity</b>	<ul style="list-style-type: none"> <li>0 to 100% with condensation</li> </ul>
<b>Ice accumulation</b>	<ul style="list-style-type: none"> <li>30mm thick on all exposed surfaces</li> </ul>
<b>Corrosion</b>	<ul style="list-style-type: none"> <li>Galvanized ASTM-A123, stainless and galvanized fasteners, multi-layer epoxy-based paint.</li> </ul>

## Shipping configuration and features

- Modular design to allow for easy shipping in standard 40ft containers.
- Rapid deployment, assembly, and commissioning at customer site.

## Ka-band performance

	Rx	Tx
Frequency (GHz)	17.70 - 21.50	27.50 - 31.00
Feed Ports	2 CP + 2 Monopulse	2 CP
Antenna Gain @ mid band	67.5 dBi	70.4 dBi
Beamwidth @ -3dB	0.07°	0.05°
G/Ts at Clear Sky @ 20° Elevation		
17.70 GHz	43.4 dB/K <sup>*1</sup>	
19.60 GHz	44.1 dB/K <sup>*1</sup>	
21.50 GHz	44.3 dB/K <sup>*1</sup>	
Power handling, per port (CW)		650 watts
VSWR (Feed interface)	1.30	1.30
Cross Pol isolation	30.8 dB	30.8 dB
Port to Port isolation Rx → Tx, Tx → Rx	85 dB	85 dB
Port to Port isolation Rx → Rx, Tx → Tx	17 dB	17 dB
Sidelobes	Meets ITU-R S-580-6	

<sup>\*1</sup>The G/T is evaluated with a 110K LNA bolted at the feed interface.